



DECLARATION OF PERFORMANCE (DoP)

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011

DoP No.: JD-T33-2026-001

1. Product Description	Column Radiator
2. Product Type	JDDH S 4012
3. Intended Use	In heating Systems in buildings
4. Manufacturer	PITACS LTD BRADBOURNE POINT, BRADBOURNE DRIVE, TILBROOK, MILTON KEYNES, BUCKINGHAMSHIRE MK7 8AT - United Kingdom
5. Authorised representative	N/A
6. System of Assessment and Verification of Constancy of Performance (AVCP)	System 3
7. Name and identification number of the notified body	Istituto Giordano S.p.A.
8. Harmonised standard	EN 442-1:2014
9. Declared Performance	
Essential characteristic	Performance
Reaction to fire	A1
Release of dangerous substances	None
Pressure tightness	no leakage at 1.3 times the maximum permissible operating pressure [1170kPa]
Surface temperature	Maximum 100°C
Pressure strength	no crack at 1.69 times the maximum permissible operating pressure [1521kPa]
Corrosion resistance	No corrosion after 100 humidity
Resistance to minor impact damage	ISO 2409:2013-1c-0

Table of thermal outputs		
Model	Heat output dT50 (W)	Heat output dT30 (W)
JDDH S 4012 1504	320	166
JDDH S 4012 1505	400	208
JDDH S 4012 1506	480	250
JDDH S 4012 1507	560	291
JDDH S 4012 1508	640	333
JDDH S 4012 1509	720	374
JDDH S 4012 1510	800	416
JDDH S 4012 1511	880	458

JDDH S 4012 1512	960	499
JDDH S 4012 1513	1040	541
JDDH S 4012 1514	1120	582
JDDH S 4012 1515	1200	624
JDDH S 4012 1516	1280	666
JDDH S 4012 1517	1360	707
JDDH S 4012 1518	1440	749
JDDH S 4012 1519	1520	790
JDDH S 4012 1520	1600	832
JDDH S 4012 1804	384	200
JDDH S 4012 1805	480	250
JDDH S 4012 1806	576	300
JDDH S 4012 1807	672	349
JDDH S 4012 1808	768	399
JDDH S 4012 1809	864	449
JDDH S 4012 1810	960	499
JDDH S 4012 1811	1056	549
JDDH S 4012 1812	1152	599
JDDH S 4012 1813	1248	649
JDDH S 4012 1814	1344	699
JDDH S 4012 1815	1440	749
JDDH S 4012 1816	1536	799
JDDH S 4012 1817	1632	849
JDDH S 4012 1818	1728	899
JDDH S 4012 1819	1824	948
JDDH S 4012 1820	1920	998
JDDH S 4012 2004	428	223
JDDH S 4012 2005	535	278
JDDH S 4012 2006	642	334
JDDH S 4012 2007	749	389
JDDH S 4012 2008	856	445
JDDH S 4012 2009	963	501
JDDH S 4012 2010	1070	556
JDDH S 4012 2011	1177	612
JDDH S 4012 2012	1284	668
JDDH S 4012 2013	1391	723
JDDH S 4012 2014	1498	779
JDDH S 4012 2015	1605	835
JDDH S 4012 2016	1712	890
JDDH S 4012 2017	1819	946
JDDH S 4012 2018	1926	1002
JDDH S 4012 2019	2033	1057
JDDH S 4012 2020	2140	1113

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

David Linger
Commercial Director

A handwritten signature in black ink, appearing to read 'D. Linger', with a large, stylized initial 'D'.

Milton Keynes, UK
20 August 2026