

Primrose Horizontal Double

Declaration of Performance



DOP No.	2608-32	Unique Product Code	NPRH
Trading Name	Primrose Horizontal Double	Type, Batch, or Serial Number	NPRH__-D-__

Manufacturer:

MHS Radiators Ltd, Unit 4 Genesis, Endeavour Drive, Basildon, SS14 3WF

Tel: 0345 521 5666 | Email: mhs@modularhg.co.uk | Website: www.mhsradiators.co.uk

System of ACVP:

System 3

Declared uses of the product, within the scope of the applicable harmonised technical specification:

Radiators for heating emission meant for permanent installation in heating systems of domestic buildings, supplied by a remote source of hot water or steam with temperature inferior to 110° C (EN 442-1-2 2014).

Notified Laboratory:

CETIAT – Centre Technique Des Industries Aerauliques et Thermiques – Notified Body Number: 1623
Domaine Scientifique de la Doua – 25, avenue des Arts – 69100 Villeurbanne

Tel: +33 0472444900 | E-mail: cetiat.commercial@cetiat.fr | Website: www.cetiat.fr

The notified body performed tests according to harmonised standard UNI EN 442 and released:

Test Report for the determination of the thermal power of an heating element:
N° 2008-138, 2008-140, 2008-141 – 24/06/2008

Pressure Resistance Test Report:
N°2008-138, 2008-140, 2008-141 – 24/06/2008

Harmonised technical specifications:

EN 442-1:2014, PCR-ed4-EN-2021 09 06,
PSR-0011-ed2.0 EN-2023 06 06, ISO 14025:2006, EN15804+A2.

Primrose Horizontal Double

Declaration of Performance



Declared performance:

Performance of the essential characteristics defined by the harmonised technical specification:

Essential Characteristics	Performance
Fire reaction	A1
Release of dangerous substances	NO
Maximum working pressure	5 bar
Pressure tightness	No leakage at 1.3 x working pressure
Pressure resistance	No leakage at 1.69 x working pressure
Maximum surface temperature	110°C
Rated thermal output	See Appendix 1
Thermal output in different operating conditions	See Appendix 1
Characteristic curve	$\Phi = K_m \times \Delta T^n$
Resistance against corrosion	No > 100h
Resistance against minor impact	Class 0

Signed for and on behalf of the manufacturer by:

Alex Bradley
Commercial Director
10/09/26

A handwritten signature in black ink that reads "ABradley". Below the signature is a dotted line.

Primrose Horizontal Double

Declaration of Performance



Appendix 1 - Declared performance:

Performance of the essential characteristics defined by the harmonised technical specification:

Rated thermal output	Dimensions mm	Output ΔT 50°C watts	Output ΔT 30°C watts	K_m	n
	448x1000	908	481	6.9969	1.2438
	616x1000	1191	634	9.4806	1.2355